

CUSTOM TRUCK BODIES AND MANUFACTURING

16339 Lima Rd., P.O. Box 686 • Huntertown, IN 46748-0686
Phone: 260-637-3177 • 800-551-9341 • FAX 260-637-6880
E-mail: hhequip@gte.net • Web: www.hhsalescompany.com

In-Bed Lift™ Platform Works Smart

H & H invented its patented In-Bed Lift™ platform cylinder body in 1979, and it's been a remarkably popular choice for cylinder handling throughout North America ever since. Here's why:

No-nonsense design for fast, efficient operation, easy maintenance. Platform stows flush

with the body floor when up, extends right to ground level when down. Twelve-volt electric/hydraulic system with push button control; power up, gravity down. Dual manual safety locks. One-year limited warranty and complete operator manual for the lift platform.



Speed up handling and delivery of cylinders and appliances

- Raise heavy gas cylinders and appliances to truck bed height at the touch of a button. Lower them to street-level just as easily. No tailgate platform to move when loading or unloading at a delivery dock. In and out fast.
- The lift platform gives you 1,056 sq in to work with. Load and unload to 1,250 lbs. with ease.
- Weatherproof controls and easy-release safety gate lock. Lift platform

stays locked in up position until you release the safety lock lever. Lock can be re-engaged when the lift platform reaches truck bed height. Controls are mounted beside lift platform, and out of the way of loaded tanks or accidental manipulation.

- The EMG Series cylinder bodies have no raised wheel wells to waste cargo space. The one-ton truck bed (shown above) measures 96" x 121.5" and holds

a maximum of forty-three 15" cylinders.


- All the standard and optional features of the complete H&H™ EMG Series, such as 3/16" heavy diamond floor plate or grated flooring option, are available on all models. Our all-steel construction body features tie-down loops, undercoating, finish painted body, and all warning labels required by D.O.T. H&H will install an EMG cylinder body on the chassis of your choice.



A built-in hydraulic lift platform lowers to street level.




Load on gas cylinders or appliances and raise them to truck bed height—all at the touch of a button.



The one-ton truck bed measures only 96" x 121.5" and holds a maximum of forty-three 15" cylinders.


Select the optional accessories you need




Safety lighting



Fire extinguisher




Side service boxes



Side service boxes offer up to 9.5 cu ft of space to outfit with shelves, drawers, tubing hangers and more. Optional double-side service boxes are also available. They provide twice the space for tools, supplies, apparel and personal items or accessories. Aluminum constructed

boxes are available as well as protective box railing. Moisture and vapor-proof safety lighting meets FMVSS-108 standards (optional LED lighting is available). For extra safety, choose the bracket mounted fire extinguisher and reflective triangle flare kit.



Double-side service boxes

Crane Selection

The Auto Crane adjustable boom Econo-Ton II all electric cranes are available on H&H™ EMG Series trucks. They feature a 2,000 lb. lifting capacity at 3 ft. 3" boom length. Manual or power rotation available.

Removable Hitch

The removable hitch is frame-mounted for security and safe transport. The hitch slides into two 2" receiver tubes and is secured with two 5/8" hitch pins and clips. Easily attached and easily removed. Your choice of a 2-5/16" ball or combination ball and pintle hook.

Specifications for EMG Series Cylinder Bodies

	10 EMG	12 EMG
Overall width	96"	96"
Overall length	121.5"	145.5"
Overall height (floor to top of rail)	38"	38"
Floor height above frame at rear axle	9"	9"
Approx. weight, including two side boxes	1,990 lb	2,300 lb
Min. truck chassis size (10 EMG)	1 ton with 60" CA	
Min. truck chassis size (12 EMG)	1 ton with 84" CA	

CONSTRUCTION

Floor 1/8" diamond plate
Floor channel members 2" x 1" x 3/16" on 12" centers
Rear bed rail opening 52"
Bed railings 1 1/2" square steel tubing
Clearance and safety lighting FMVSS-108 Standards

STANDARD


OPTIONAL CONSTRUCTION FEATURES

Floor 3/16" diamond floor plate
or 3/16" x 1" open bar grate
with 4" x 1" openings
(Floor structural channel members 3" x 4.1#)

ALL STEEL SIDE SERVICE BOXES

Dimensions 36"W x 34"H x 14"D overall
Shell 16-gauge with protection angles welded top and bottom of shell.
Door 18-gauge double-panel galvanized steel. Doors have recessed paddle handle, safety striker plates, cylinder locks keyed alike, two keys and door stop. Weatherstripping.
72" L Double-side service boxes available.

Specifications subject to change without notice.



Prices: See H&H EMG Series Price List

Order Instructions: Please specify H&H optional features, paint color/code, truck make, model and wheel base.

